

Type Overview

Differential Pressure Sensor (Water)

Active sensor (0 to 10 V) for measuring the differential pressure in liquid or dry media. Various pressure ranges, rugged NEMA 4 / IP65 and compact stainless steel housing.

Optional stainless steel or brass pipe connection adapters also available.





	Туре	Measuring Range Pressure	Output Signal Active Pressure	Overpressure Limit	Overpressure Limit Note	Maximum System Pressure	
	22WDP-511	015 psi	DC 010 V	85 psi	Single-sided	300 psi	
	22WDP-512	030 psi	DC 010 V	85 psi	Single-sided	300 psi	
	22WDP-514	050 psi	DC 010 V	230 psi	Single-sided	300 psi	
	22WDP-515	0100 psi	DC 010 V	230 psi	Single-sided	300 psi	
Technical Data							
	Electrical Data	Power Supply DC		1524 V	1524 V, ±10%, 0.37 W		
		Power Supply AC		24 V, ±10	24 V, ±10%, 0.9 VA		
		Electrical Connection		plug for w	plug for wire 15 GA [0.5 to 1.5 mm ²]		
		Cable Entry		• .	angle plug according to DIN 43650, construction A		
	Functional Data	Output Signal Active Note		voltage o	voltage output: min. 2 kΩ load		
		Mechanical Connection		pressure	pressure connector: 1/4" NPT		
		Mounting		installatio	n position unrest	ricted	
		Media		water			
	Measuring Data	Measured Values		differentia	differential pressure		
		Measuring media		air and no	air and non-aggressive gases		
		Accuracy Pressure			<±1% of measuring range @ 23°F to 167 °F [-5°C to 75°C]		
	Materials	Body Seal		EPDM	EPDM		
			Housing		base: stainless steel 1.4305 cover: aluminum pressure die casting		
		Material Contacting the Medium		stainless	stainless steel 1.4301, ceramic		
	Safety Data	Ambient Temperature		15°F to 1	15°F to 120°F [-10°C to 50°C]		
	Medium Temperature		15°F to 1	15°F to 175°F [-10°C to 80°C]			
		Protection Class I	IEC/EN	III protect	ive extra-low volt	age (pelv)	
		Protection Class	UL	UL Class	2 Supply		
		EU Conformity		CE Marki	ng		
		Degree of Protect	tion IEC/EN	IP65			
		Degree of Protect	tion NEMA/ UL	NEMA 4			
		Quality Standard		ISO 9001			

Weight


0.55 lbs



Accessories

Optional Accessories	Description	Туре	
	pipe connector brass, 2 pcs., Pipe 0.24" [6 mm] to 1/4" NPT (external thread)	A-22WP-A03	
	pipe connector stainless steel, 2 pcs., Pipe 0.24" [6 mm] to 1/4" NPT (external thread)	A-22WP-A05	
	pipe connector brass, 2 pcs., Pipe 0.3" [8 mm] to 1/4" NPT (external thread)	A-22WP-A07	
	pipe connector stainless steel, 2 pcs., Pipe 0.3" [8 mm] to 1/4" NPT (external thread)	A-22WP-A09	

Wiring Diagram



Dimensions

