



CARBON™ WALL MOUNT ENCLOSURE

CR6U61001

Wall mount enclosure safeguards 6U of 19" rack equipment

The CR6U61001 is designed for use in network closets, classrooms and other locations. This wall mount enclosure houses network switches and patch panels up to 22" deep. It includes convenient top panel cable access openings, perforated front door and side panels for efficient airflow, adjustable rack angles, and square and threaded mounting holes. The CR6U61001 ships fully assembled for quick deployment, and can be customized with compatible accessories. It is covered by a 5-year limited warranty.

FEATURES

- Rack Type: Wall Mount Enclosure
- Height: 6U
- Stationary Capacity: 132 lbs
- Max. Mounting Depth: 22.2"
- Mounting Hole Types: Square and Threaded
- Warranty: 5 Years

TYPICAL APPLICATIONS

- Network Closets
- Retail Locations
- Back Office
- Classrooms



SPECIFICATIONS

PHYSICAL		PHYSICAL - CONT.	
Rack Height	6U	Weight Capacity - stationary load (lbs)	132.3
Color	Black RAL 9005 powder coat paint	Weight Capacity - stationary load (kg)	60
Door Type	Hex Perforated Metal Door	Factory Default Mounting Depth (in)	17.2
Rack Angle Mounting Hole Type	Square and #12-24 Mounting Hole	Factory Default Mounting Depth (mm)	436

CARBON™ WALL MOUNT ENCLOSURE

CR6U61001



SPECIFICATIONS CONT.

PHYSICAL - CONT.

Cable Access Opening Dimensions (in)	9.8 x 2.2
Cable Access Opening Dimensions (mm)	250 x 56
Max. Mounting Depth (in)	22.2
Max. Mounting Depth (mm)	562
Min. Mounting Depth (in)	1.9
Min. Mounting Depth (mm)	47
Dimensions (WxHxD in.)	23.6 x 14.6 x 23.6
Dimensions (WxHxD mm)	600 x 372 x 600
Net Weight (lbs)	37.2
Net Weight (kg)	16.9
Shipping Dimensions - WxHxD (in)	26.18 x 17.12 x 26.18
Shipping Dimensions - WxHxD (mm)	665 x 435 x 665
Shipping Weight (lbs)	41
Shipping Weight (kg)	18.6

SPECIAL FEATURES

Numbered Rack Units	Yes
Rolling Casters	Optional
Removable Door and Side Panels	Yes
Reversible Front Door	Yes
Lockable Door and Side Panels	Yes, keyed alike
Ventilation	Perforated Door and Side Panels with Ventilated Top and Bottom
Cable Access	Top and Bottom Openings
PE Grounding Point	Yes

ENVIRONMENTAL

Protection Class	IP20
------------------	------

CERTIFICATIONS

Certifications	CE
Approvals	DIN41491, DIN41494, EIA/ECA-310-E, IEC 60297-3-100, RoHS

WARRANTY

Product Warranty	5 Years Limited
------------------	-----------------