

P545

P545 Series Electronic Lube Oil Control

Description

The P545 Series Electronic Lube Oil Control is designed for use on refrigeration compressors equipped with an oil pump that accepts a single-point differential pressure switch. The P400 switch continuously monitors net lube oil pressure and the P545 control locks out the compressor if lube oil pressure falls below the manufacturer's recommended net pressure for longer than the recommended lube oil time delay. Front-mount Light-Emitting Diodes (LEDs) indicate the status of the lubrication system, and a user-selectable, minimum-off time delay can be set to minimize compressor short cycling.

A Johnson Controls/PENN® R310AD Current Sensing Switch, sold separately, may be used to disable the P545 control lockout circuit during abnormal compressor shutdowns.

Features

- Single-Pole Double-Throw (SPDT) relay contacts for liquid line solenoid and alarm applications - allows liquid line solenoid to be closed if the P545 control shuts off the compressor due to low oil pressure; provides alarm indication, including circuits that use neon lights.
- relay contact output for compressor - provides reliable, long-lasting operation
- built-in test circuit - verifies proper control operation quickly, without additional tools or equipment
- improved noise immunity - exceeds immunity requirements of UL 991 for transient overvoltage: IEC 61000-4-3 for radiated Radio Frequency (RF) and IEC 61000-4-6 for RF-induced conducted disturbances
- selection of anti-short cycle time delay - allows choice of anti-short cycle strategy for a wide range of equipment requirements; possible elimination of external short-cycle timer



P545 Control with P400 Switch

- user-friendly display panel - displays the status of the compressor lubrication system continuously
- backwards compatibility - allows easy replacement of existing electronic lube oil controls

Selection Charts

P545

Product Code Number	Lube Oil Delay (Seconds)	P400 Switch	Wiring Harness	Fits Compressors Manufactured by
P545NCB-22C ¹	120	P400AD-2	WHA-P400-100	Copeland®
P545NCB-25C ¹	90	P400BD-1	WHA-P400-125	Bitzer
P545NCB-82C ¹	120	P400AD-1	WHA-P400-100	Carlyle®

1. Switch and wiring harness included

Control and Sensor/Switch Compatibility

Test	P345 or P445 Control with P300 Sensor	P345 or P445 Control with P400 Switch	P545 Control and P300 Sensor	P545 Control and P400 Switch
Wiring Harness ¹	WHA-P300-xxx only	WHA-P300-xxx or WHA-P400-xxx	WHA-P300-xxx only	WHA-P300-xxx or WHA-P400-xxx
Test Switch	6-8 Second delay	Does not function ²	Immediate	Immediate

1. WHA-P300-xxx is the 3-wire harness supplied with the P345 or P445 control and the P300 sensor. WHA-P400-xxx is the 2-wire harness supplied with the P545 control and the P400 switch.

2. When the P445 control is wired to a P400 switch, The **Test** button may operate when first powered up; however, after a couple minutes of operation, the **Test Switch** function no longer works. All other control functions operate normally.

Accessories

P400 Single-Point Differential Lube Oil Pressure Switch

Product Code Number ¹	Open Point (Differential Pressure)	Close Point (Differential Above Open Point)	Threads	Wiring Harness
P400AD-1C	7.0 ±1.0 psid	less than or equal to 2.0 psid	3/4-16 UNF	WHA-P400-100
P400AD-2C	12.75 ±0.75 psid	less than or equal to 1.5 psid		
P400BD-1C	10.0 ±1.5 psid	less than or equal to 3.0 psid	M20 x 1.5	WHA-P400-125

1. Wiring harness included

P545 Series Electronic Lube Oil Control (Continued)

Wiring Harnesses and Other Accessories

Product Code Number	Description
KITP545-82C ¹	CST29A-600C sensor block; P545NCB-82 control; P400AD-1C switch WHA-P400-100C wiring harness
WHA-P400-100C	3-1/3 ft (1 m) length wiring harness
WHA-P400-125C	4 ft (1-1/4 m) length wiring harness
WHA-P400-250C	8 ft (2-1/2 m) length wiring harness
WHA-P400-430C	14 ft (4-1/3 m) length wiring harness
R310AD-1C	Low-voltage Current Sensing Switch
271-51	Universal Mounting Bracket

1. Contact Carlyle Compressor Co. at 1-800-462-2759 to order Sensor Block Gasket 06DA680063.

Technical Specifications

P545NCB Electronic Lube Oil Control	
Power Requirements	120 or 240 VAC, 50/60 Hz +10%, -15%; power consumption: 3 VA
Open Point (Differential Pressure)	P545NCB-22/P400AD-2: 12.75 ± 0.75 psid (87.9 ± 5.17 kPa) P545NCB-25/P400BD-1: 10 ± 1.5 psid (68.9 ± 10.3 kPa) P545NCB-82 P400AD-1: 7 ± 1.0 psid (48.2 ± 6.9 kPa)
Lube Oil Time Delay (Factory Settings)	P545NCB-22: 120 ± 15 seconds P545NCB-25: 90 ± 12 seconds P545NCB-82: 120 ± 15 seconds
Anti-short Cycle Timer	Four selectable positions: 0, 35, 65, and 100 seconds (nominal times)
Type of Refrigerant	Non-corrosive refrigerants only
Electrical Connections	Control: Screw type terminals on a barrier terminal strip Sensor: Snap-connect at sensor end, 3-pin plug at control end
Maximum Electrical Rating	Isolated relay output to compressor contactor (M-1 and M-2) Pilot duty 375 VA at 120 VAC, 750 VA at 240 VAC
Alarm Circuit (Relay)	NOA contact: Pilot duty 125 VA at 120/240 VAC; 60 W tungsten at 120/240 VAC NCA contact: Pilot duty 125 VA at 120 VAC, 250 VA at 240 VAC
Backplate Material	0.062 in. (1.6 mm) cold rolled steel
Case and Cover Material	High impact thermoplastic
Ambient Operating Conditions	-40 to 131°F (-40 to 5°C)
Ambient Storage Conditions	-40 to 185°F (-40 to 85°C)
Approximate Shipping Weight	1.80 lb (0.82 kg)
Agency Listings	UL Listed, File SA516, CCN SDFY UL Listed for Canada, File SA516, CCN SDFY7