


D352 Series

Pressure Display Module



D352



Description

The D352 Display Module is used in conjunction with the P352 and P352P Series Pressure Controls. A 3-digit LCD display provides continuous readout of the actual pressure sensed by the P99, P399, or DPT-2640 Transmitter. By pressing and holding the setpoint button for three seconds, the pressure setpoint will be displayed.

Features

- display of actual system pressure and setpoint
- remote display mounting with WHA29A cable (up to 50 ft)
- 5-pin connector simplifies wiring between modules

Applications

- pressure indication (local or remote) in conjunction with P352 and P352P Pressure Controls

To Order

Specify the code number from the following selection chart.

Selection Chart

Code Number	Display Range	Display Characters
D352AA-1C	0 to 435 psig	3-digit 0.35 in LCD
D352CA-1C	0 to 9.99 in. W.C.	
D352CA-2C	0 to 0.999 in. W.C.	
D352AA-2C	0 - 750 psi	

Accessories

For remote mounting of the D352 Display Module, specify the code number and cable length from the Accessories table below.

Code Number	Cable Length
WHA29A-600R	3 ft (0.9 m)
WHA29A-603R	25 ft (7.6 m)
WHA29A-604R	50 ft (15.2 m)

Specifications

D352 Pressure Module with psig or in. W.C. Scale	
Case and Cover Material	NEMA 1, high-impact thermoplastic
Read-out	3-digit LCD (Liquid Crystal) continuous display
Input Voltage	D352AA-2C 5 VDC provided by the P352 Pressure Control
	D352AA-1C 14 VDC provided by the P352 Pressure Control
	D352CA-1C
	D352CA-2C
Ambient Temperature	Operating -30 to 150°F (-34 to 66°C)
	Shipping -40 to 167°F (-40 to 75°C)
Ambient Humidity	0 to 95% RH non-condensing
Mounting	Surface or DIN rail

D352 Dimensions, in. (mm)

