

A19

Water Chiller Control (With Locked Cut-Out/Adjustable Cut-In)



A19ZBA-1

Description

Remote bulb temperature control with limited set point range, adjustable differential, and adjustable cut-out.

Features

- adjustable cut-out (38 to 47°F)
- wide differential adjustment range

Accessories

- includes Part No. FTG13A-600R packing nut as standard
- replacement cover: CVR61A-600R

Applications

- water chillers

Specifications

- maximum bulb temperature: 140°F (60°C)

To Order

Specify the code number from the following selection chart.

Selection Chart

Code Number	Switch Action	Range °F (°C)	Diff F° (C°)	Bulb and Capillary	Bulb Well No. (order separately)	Range Adjuster
A19ZBA-1C	SPST Close High Open Low	38 to 80 (3 to 27)	8 to 40 (4 to 22) Adjustable	3/8 in. x 3 7/16 in. 6 ft Cap.	WEL14A-602R	Knob

Electrical Ratings

Motor Ratings VAC	120	208	240
AC Full Load Amp	16.0	9.2	8.0
AC Locked Rotor Amp	96.0	55.2	48.0
Non-Inductive or Resistance Load Amp (Not Lamp Loads)	16.0	9.2	8.0
Pilot Duty – 125 VA, 24 to 277 VAC			