



Functional Devices, Inc.
310 South Union Street
Russiaville, IN 46979
www.FunctionalDevices.com

Office 765.883.5538
Sales 800.888.5538
Fax 765.883.7505
Email sales@functionaldevices.com

PSM19A24DAS

DC POWER SUPPLY

4.00" & 2.75" Track Mount Isolated Linear DC Power Supply, 120 Vac to 1.5-28 Vdc, 300 mA Adjustable Output



SPECIFICATIONS

Voltage Input: 120 Vac
Voltage Output: 1.5 - 28 Vdc Isolated
Frequency: 50/60 Hz
Overload Protection: Electrical and Thermal, Auto-Reset
Operating Temperature: -30 to 140° F
Status: LED On = Activated

Dimensions: 1.625" x 2.750" x 4.000"
Track Mount: 4.000" and 2.750"
MT212-4 Mounting Track Supplied
Weight: 1.10 lbs.

ON/OFF Switch: 2 Position Toggle

Approvals: Class II UL Listed, UL916, C-UL, CE

Output Current Ratings:

116 mA @ 10 Vdc
125 mA @ 12 Vdc
300 mA @ 24 Vdc

Input Current Rating:

150 mA Maximum

Percent Ripple:

0.0016%, 24 Vdc @ 300 mA

Regulation:

Load: 0.04% No Load to Full Load
Line: 0.6250 mV/V

VOLTAGE OUTPUT
Adjustable From 1.5-28 Vdc

TOGGLE
SWITCH:

On / Off



VOLTAGE INPUT
120 Vac

NOTES