

## RIBL3C

### 10 AMP PILOT CONTROL RELAY

Enclosed Relays 10 Amp 3 SPST-N/O with 10-30 Vac/dc Coil



#### SPECIFICATIONS

**# Relays & Contact Type:** Three (3) SPST Continuous Duty Coil  
**Expected Relay Life:** 10 million cycles minimum mechanical  
**Operating Temperature:** -30 to 140° F  
**Operate Time:** 20ms  
**Relay Status:** LED On = Activated  
**Dimensions:** 4.00" x 4.00" x 1.80" with .50" NPT nipple  
**Wires:** 16", 600V Rated  
**Approvals:** UL Listed, UL916, UL864, C-UL  
California State Fire Marshal, CE  
**Housing Rating:** Plenum, NEMA 1  
**Gold Flash:** Yes  
**Override Switch:** No

#### Contact Ratings:

10 Amp Resistive @ 120-277 Vac  
10 Amp Resistive @ 28 Vdc  
480 VA Pilot Duty @ 240-277 Vac  
480 VA Ballast @ 277 Vac  
600 Watt Tungsten @ 120 Vac N/O  
240 Watt Tungsten @ 120 Vac N/C  
1/3 HP for N/O @ 120-240 Vac  
1/6 HP for N/C @ 120-240 Vac  
1/4 HP for N/O @ 277 Vac  
1/8 HP for N/C @ 277 Vac

#### Coil Current:


30 mA @ 10 Vac 12 mA @ 10 Vdc  
32 mA @ 12 Vac 14 mA @ 12 Vdc  
42 mA @ 24 Vac 16 mA @ 24 Vdc  
50 mA @ 30 Vac 18 mA @ 30 Vdc

#### Coil Voltage Input:

10-30 Vac/dc ; 50-60 Hz  
Drop Out = 2.1 Vac / 2.8 Vdc  
Pull In = 9 Vac / 10 Vdc

#### Notes:

» Order Normally Closed by adding "-NC" to end of model number



## NOTES