

Functional Devices, Inc. 310 South Union Street Russiaville, IN 46979 www.FunctionalDevices.com Office 765.883.5538 Sales 800.888.5538 Fax 765.883.7505 Email sales@functionaldevices.com

TRANSFORMER **TR150VA001** Transformer 150 VA, 120 to 24 Vac, Circuit Breaker, Foot and Single Threaded Hub Mount → 1.300" | Wht - 120 Vac Yel/Wht - 24 Vac* (+)+ LISTED ξ SECONDARY WIRES PRIMARY WIRES CE .225 Blk - Comm Yel - Comm *Secondary Yel/Wht wire in phase with -Primary Blk wire. RoHS 2.500" SPECIFICATIONS Mounting Hole = $.400" \times .200"$ VA Rating: 150 Frequency: 50/60 Hz 3.500" 3.790" Mounting: Foot & Single Threaded Hub **Over Current Protection:** Circuit Breaker C Dimensions: 3.250" x 3.790" x 3.500" (w/ .500" NPT Hub) Wire Length: 9.5" Typical w/ .5" Strip Operating Temperature: -30 to 140° F 3.250" MTBF: 100,000 Hours @ 77° F Construction: Split-Bobbin -9.50" → - .50" Weight: 4.92 lbs. Approvals: UL506 Listed General Purpose C-UL, CE, RoHS 0 0

NOTES