



Advanced Electronic Time Controls 1, 2, and 4 Channels



| Talento 400/800 Series Ordering Data | | | | |
|--------------------------------------|-------------------|----------|----------|----------|
| Grasslin/Intermatic Model | Voltage | Output | Channels | Programs |
| Mechanism Only | | | | |
| TALENT0471-120 | 120VAC, 50/60Hz | 16A SPDT | 1 | 30 |
| TALENT0891-24 | 24VAC/DC, 50/60Hz | 16A SPDT | 1 | 400 |
| TALENT0891-120 | 120VAC, 50/60Hz | 16A SPDT | 1 | 400 |
| TALENT0472-120 | 120VAC, 50/60Hz | 16A SPDT | 2 | 30 |
| TALENT0892-24 | 24VAC/DC, 50/60Hz | 16A SPDT | 2 | 400 |
| TALENT0892-120 | 120VAC, 50/60Hz | 16A SPDT | 2 | 400 |
| TALENT0894-24 | 24VAC/DC, 50/60Hz | 16A SPDT | 4 | 400 |
| TALENT0894-120 | 120VAC, 50/60Hz | 16A SPDT | 4 | 400 |
| NEMA 1 Indoor Enclosure | | | | |
| GMX471-I-120 | 120VAC, 50/60Hz | 16A SPDT | 1 | 30 |
| GMX891-I-120 | 120VAC, 50/60Hz | 16A SPDT | 1 | 400 |
| GMX472-I-120 | 120VAC, 50/60Hz | 16A SPDT | 2 | 30 |
| GMX892-I-24 | 24VAC/DC, 50/60Hz | 16A SPDT | 2 | 400 |
| GMX892-I-120 | 120VAC, 50/60Hz | 16A SPDT | 2 | 400 |
| GMX894-I-24 | 24VAC/DC, 50/60Hz | 16A SPDT | 4 | 400 |
| GMX894-I-120 | 120VAC, 50/60Hz | 16A SPDT | 4 | 400 |

SRS 3800

7 Day, 8-Channel End Time Switch

APPLICATION: Time of day ON/OFF control of 8 circuits of HVAC systems, zone heating, industrial processes, alarm systems, lighting, fans, pumps or other loads in commercial, industrial, institutional, and agricultural facilities. A simple and effective energy management system for small and mid-sized office buildings, schools, banks, malls, and government buildings.

Specifications:

- Input Voltage** – 120VAC 50/60 Hz
- Output Rating** – 10A Resistive @ 120-240VAC per channel
- Output Configuration:** 6 SPDT, 2 SPST (NO)
- Power Consumption:** 12VA
- Shortest Switching Time:** 1 minute
- Ambient Temperature:** 14°F to 122°F (-10°C to 50°C)
- Ambient Humidity:** 0 to 95% RH, non-condensing
- Manual 3-Way Override:** Auto-On-Off
"ON" or "OFF" status indicator for each channel
- Wiring Connections:** Screw terminals, 12-24AWG
- Size:** 8.38 (213mm) x 7.08" (180mm) x 4.5" (114mm)

| SRS 3800 Ordering Data | | | | |
|--------------------------------|--------------|----------------------|----------|----------|
| Grasslin/Intermatic Model | Voltage | Output | Channels | Programs |
| Plastic Clear Enclosure | | | | |
| SRS3800-120 | 120VAC, 60Hz | 10A, 6-SPDT & 2-SPST | 8 | 224 |

Features:

- 8 channels programmable independently or simultaneously
- 7 day programming
- 2 ON and 2 OFF settings per day
- ON-OFF-AUTO Override for each channel
- Holiday "OFF" provision
- Indoor/Outdoor enclosure w/clear door
- Battery backup for 1 month
- 10 Amp, SPDT switching

