

Description: 18 AWG 8/C Str Shielded CMP-CL2P  
Specifications: UL Standards 13, & 444; NEC Article 725

**Construction:**

Conductor 18 AWG 16/30 Stranded Bare Copper  
Insulation PVC Plenum  
Insulation Thickness 0.007" nom.  
Insulation Colors Blk,Wht,Red,Grn,Blu,Brn,Ylw,Org  
Insulation Diameter 0.060 nom.  
Lay Length 4.0" nom.  
Drain Wire 22 7/30 TC  
Shield 0.001" Thick Aluminum/Mylar

Jacket PVC Plenum  
Color Natural  
Jacket Thickness 0.016" nom.  
Outside Diameter 0.236" nom.  
Legend (Ink Print) HONEYWELL 18 AWG 8/C (ETL) CMP-CL2P 3038058 (RoHS) W/O# XXXXXX-XXX C(ETL) FT6  
XXXXX FT RM# A B C D E F 1 2 3 4 5 6 7 8

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 60 pf/ft nom.  
Impedance 34 Ohms nom.  
DC Resistance 6.5 Ohms/M' at 20°C  
Flame Rating UL910, CSA FT6