

# GPS-iMEASURE™

## Wall Mounted Ion Meter

### Product Description

The GPS-iMEASURE is the first commercially available ion detector that can be permanently mounted in the space to measure ion levels in real time and provide a signal to a BAS.

### Standard Features

Auto Calibration, Auto Zero, 0-10VDC Output for BAS Monitoring 24/7, Watchdog Timer, Bi-color LED and 0 - 1,000,000 ions/cc Range.

### Benefits

The GPS-iMEASURE provides monitoring of ionization levels remotely without having to manually take measurements with a handheld meter.




### Specifications

Input Voltage	12 - 24VDC
Amps	100mA
Power	2.4 Watts
Unit Dimensions/Weight	2.0"L x 4.25"W x 3.25"H / 0.49 lbs
Output Voltage	0 - 10VDC
Ion Sensing Range	0 - 1,000,000 ions (+ or -)
Output Impedance	1000 ohm
BAS Scaling	Adjustable
Humidity Range	0 - 90% RH non-condensing
Internal Jumper	Adjusted in field to desired ion range
Compliance	OSHPD Seismic (OSP)

### Applications

- Can be used with any ion producing GPS system.



Engineering Air for a Cleaner World™

Global Plasma Solutions, Inc.  
[www.GlobalPlasmaSolutions.com](http://www.GlobalPlasmaSolutions.com)