

Fuse terminal with illuminated indicator (30-60V) for G fuse links 5x 20, 5x 25 and 5x 30 mm with 4 mm² spring-loaded connection, Width: 6.2mm, Color: black



Figure similar

| Model | |
|---|--------------------|
| product brand name | ALPHA |
| type of light source / as fault indicator | LED |
| design of the fuse link | glass fuse 5x20 mm |
| design of fuse holder | pluggable |
| General technical data | |
| insulation material | others |
| terminal contact spacing | 6.2 mm |
| Supply voltage | |
| operating voltage / rated value | 250 V |
| type of voltage / for supply of the fault indicator | others |
| Protection class | |
| combustibility class acc. to UL 94 | V0 |
| Main circuit | |
| operating current / rated value | 6.3 A |

| Appearance | |
|------------|-------|
| color | black |

| Product details | |
|---|----|
| product component / required / connection plate | No |

| Number | |
|---------------------------|---|
| number of terminal levels | 1 |

| Connections | |
|---|------------------------|
| wire stripping length | 12 mm |
| connectable conductor cross-section / solid | |
| • minimum | 6 mm ² |
| • maximum | 6 mm ² |
| connectable conductor cross-section / stranded | |
| • minimum | 6 mm ² |
| • maximum | 6 mm ² |
| connectable conductor cross-section / finely stranded | |
| • with core end processing / minimum | 4 mm ² |
| • with core end processing / maximum | 4 mm ² |
| • without core end processing / minimum | 4 mm ² |
| • without core end processing / maximum | 4 mm ² |
| type of electrical connection | |
| • 1 | spring-loaded terminal |
| • 2 | spring-loaded terminal |
| position / of the terminal | top |

| Mechanical Design | |
|---|----------------|
| height / with lowest-profile installation | 62.5 mm |
| length | 61.5 mm |
| mounting type | DIN rail 35 mm |
| material / of the insulating body | Other |

Certificates

| General Product Approval | Declaration of Con- formity | other |
|--------------------------|--------------------------------|-------|
|--------------------------|--------------------------------|-------|



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=8WH2000-1JG68>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH2000-1JG68>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2000-1JG68

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>