

Fuse terminal with illuminated indicator (110-250V) for G fuse links
6x 32 mm with 4 mm² spring-loaded connection, Width: 8.2mm,
Color: black



Figure similar

Model	
product brand name	ALPHA
type of light source / as fault indicator	LED
design of the fuse link	glass fuse 6.3x32 mm
design of fuse holder	pluggable
General technical data	
insulation material	others
terminal contact spacing	8.2 mm
Supply voltage	
operating voltage / rated value	400 V
type of voltage / for supply of the fault indicator	others
Protection class	
combustibility class acc. to UL 94	V0
Main circuit	
operating current / rated value	10 A

Appearance	
color	black

Product details	
product component / required / connection plate	No

Number	
number of terminal levels	1

Connections	
wire stripping length	12 mm
connectable conductor cross-section / solid	
• minimum	6 mm ²
• maximum	6 mm ²
connectable conductor cross-section / stranded	
• minimum	6 mm ²
• maximum	6 mm ²
connectable conductor cross-section / finely stranded	
• with core end processing / minimum	4 mm ²
• with core end processing / maximum	4 mm ²
• without core end processing / minimum	4 mm ²
• without core end processing / maximum	4 mm ²
type of electrical connection	
• 1	spring-loaded terminal
• 2	spring-loaded terminal
position / of the terminal	top

Mechanical Design	
height / with lowest-profile installation	69 mm
length	76.5 mm
mounting type	DIN rail 35 mm
material / of the insulating body	Other

Certificates

General Product Approval	Declaration of Con- formity	other
--------------------------	--------------------------------	-------



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=8WH2000-1RG08>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH2000-1RG08>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2000-1RG08

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>