

V-6135

Three-Way Air Switching Valve



Description

The V-6135 Three-Way Air Switching Valve switches the flow of air from one air line to another. The valve functions as a selector or diverter and provides no exhaust function.

Features

- fast acting two-position switching mechanism
- narrow deadband between output modes eliminates the possibility of the N.C. and N.O. ports being open at the same time
- factory supplied with an integral mounting bracket for surface mounting

Applications

- · Day-night switching
- · Heating-cooling
- · Enthalpy switchover

Repair Parts

Replace unit.

To Order

Specify the code number from the following selection chart.

Selection Chart

Code Number	Description	
V-6135-1		Between 2 and 4 psig (14 and 28 kPa)
V-6135-2		Between 11 and 15 psig (77 and 105 kPa)
V-6135-3		Between 15 and 19 psig (105 and 133 kPa)

Accessories

Code Number	Description	
V-6135-100	Barbed Fitting Kit for 1/4 in. O.D. Polytubing	

Specifications

V-6135 Three-Way Air Switching Valve			
Switchover - Pressure	V-6135-1	Between 2 and 4 psig (14 and 28 kPa)	
	V-6135-2	Between 11 and 15 psig (77 and 105 kPa)	
	V-6135-3	Between 15 and 19 psig (105 and 133 kPa)	
Air Connections		Polytubing, 5/32 or 1/4 in. O.D.	
Fitting Type		Barbed	