

T-5210

# Pneumatic Temperature Transmitter



## Description

The T-5210 Pneumatic Temperature Transmitter measures temperature and converts this measurement to an air pressure signal that is transmitted to a pneumatic receiver, controller, or receiver-indicator. When used with a Dewcel<sup>®</sup> (purchased locally), the T-5210 operates as a dew point transmitter.

## Features

- provides an exact proportional relationship between the measured temperature and the transmitted signal

- includes appropriate brackets for mounting to ductwork, walls, or directly to the hub of a duct flange, or separable well
- operates in any position from a rigid, flat, mounting surface
- requires a 0.007 in. restricted supply

## Repair Parts

If the product fails to operate within its specifications, unit replacement is required.

## To Order

Specify the code number from the following selection chart.

## Selection Chart

Code Number	Description		
	Element Style	Operating Range	
T-5210-1001	Copper Bulb with 5-1/2 in. (140 mm) Copper Capillary	50 to 100°F	
T-5210-2002		0 to 100°C	
T-5210-2003		-15 to 35°C	
T-5210-1002		0 to 100°F	
T-5210-1004		40 to 240°F	
T-5210-1008		50 to 150°F	
T-5210-1123		60 to 85°F	
T-5210-2001		10 to 35°C	
T-5210-1125		40 to 65°C	
T-5210-1113		Copper Bulb with 4 ft (1.2 m) Copper Capillary	-40 to 160°F
T-5210-2004	-40 to 60°C		
T-5210-1144	-20 to 80°F		
T-5210-1114	0 to 100°F		
T-5210-2005	-15 to 35°C		
T-5210-1151	20 to 120°F		
T-5210-1135	200 to 400°F		
T-5210-1007	8 ft (2.4 m) Copper Averaging Element with 1 ft (305 mm) Copper Capillary		50 to 150°F
T-5210-1006			40 to 240°F
T-5210-1009			0 to 100°F
T-5210-1124		40 to 65°F	
T-5210-2006		0 to 50°C	
T-5210-2007		-15 to 35°C	
T-5210-1150		20 to 120°F	
T-5210-1005		50 to 100°F	
T-5210-1116		17 ft (5.2 m) Copper Averaging Element with 1 ft (305 mm) Copper Capillary	50 to 150°F
T-5210-1118			0 to 100°F
T-5210-2008		-15 to 35°C	

## Accessories

Code Number	Description
T-275-100	"B" Bulb Element Holder
T-275-101	Averaging Element Holder
T-800-1603	Single-Hub Duct Flange
T-800-1604	Double-Hub Duct Flange
T-800-1605	Brass Well, 6-1/2 in.
T-800-1606	Stainless Steel Well, 5-1/4 in.
TE-6001-8	Temperature Element Holder
T-1800-1610	Bulb Element Adapter Nut, 1/2 in. NPT
T-800-1618	Brass Well, 9-1/2 in.
T-800-1620	Stainless Steel Well, 9-1/2 in.
T-800-1624	Dual Brass Well, 6-1/2 in.
T-5210-129	Sheet Metal Bracket
T-5210-138	Dewcel <sup>®</sup> Adapter Kit
T-5210-602	Pneumatic Transmitter Cover Kit, includes one Blank Cover and two Pan-Head Mounting Screws
SHL10A-603R	Bulb Weather Shield
R-3710 Series	0.007 in. Aqua-colored Restrictor