

20-601, 20-602: CHAIN LEVER WATER GAUGES



OVERVIEW

Lever on standard 12-foot chain allows operator to open and close valves that would be beyond reach. Valve stems operate on quarter-turns.

FEATURES

- Quick opening, non-automatic
- Service rating: 250 psig @ 400°F, 500 psig @ 100°F (See note!)
- EPDM standard gauge glass gasket
- Standard 1/4" needle drain valve
- Furnished with 12 feet of chain
- H-2485 pull handle is standard
- CRN Registered

| Part Number | Pipe Size (in.) | Glass O.D. & Length | Wt./100 (lbs.) |
|----------------|--------------------|------------------------|-------------------|
| 20-601-00## | 1/2 | 5/8 x 12 | 370 |
| 20-602-00## | 3/4 | 3/4 x 16 | 435 |

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets. **Ball valve not included. Includes 1/4" needle drain.

OPTIONS

| Suffix Number | Specification |
|------------------|--|
| -00 | Standard gauge w/ standard glass & rod |
| -01 | Top only |
| -02 | Bottom only |
| -03 | Standard gauge less glass & rod |
| -10 | For special gauges w/ non-standard glass and rod lengths |