



23-600: Stainless Steel Expansion Tank Gauges



Overview

Holds all 316 stainless steel-compatible liquids. In lower arm: shut-off valve and stainless steel drain valve.

Features

- Two stainless steel guard rods
- High pressure glass standard
- CRN Registered
- 250 psig at 406°F: maximum working pressure (NOTE: Service ratings are subject to pressure / temperature ratings of gauge glass and glass gaskets. Regular gauge glass is used in the standard water gauges unless otherwise noted as red line or high pressure.)

Dimensions

Part No.	Size	WT/100 lbs./kg	GLASS O D & LENGTH	Wheel Type
23-651-00	1/2 15	225.000 102.058	5/8" x 12" 16 x 300	Aluminum
23-654-00	3/4 20	225.000 102.058	5/8" x 12" 16 x 300	Aluminum

Options

Suffix Number	Specification
-00	Standard Gauge w/ Standard Glass & Rod
-01	Top only
-02	Bottom only
-03	Standard Gauge Less Glass and Rod
-10	For Special Gauges and Gauges With Non-Standard Glass and Rod Lengths
NOTE	Service ratings are subject to pressure / temperature ratings of gauge glass. Regular gauge glass is used in the standard water gauges unless otherwise noted as red line or high pressure